

Coaxial Relay TOHTSU

CX-140D-24V



Mechanical Characteristics

Contact Arrangement		SPDT
Operational Temperature		- 25 °C to + 50 °C
Max Temperature Rise		20 °C
Weight		Approx. 95 g
Mounting		Four screws
Cable Connections		One N-female, directly connect cables

Electrical Characteristics

Impedance		50 Ohms
Nominal Voltage		24 V DC
Voltage Range		20 V DC - 26 V DC
Current		40 mA @24 V DC 20 °C
Coil Resistance		600 ±10% Ohms @ 20 °C

RF-Properties

Frequency	VSWR	Isolation	Ins. Loss	RF Power input
MHz	max	-dB(min) ±3 dB	-dB(max)	W
50	1.03	55	0.08	250
150	1.03	51	0.10	250
500	1.05	47	0.15	200
1000	1,06	34	0.20	150
1500	1.20	28	0.25	100

Actuation Data

Pull In		20 V DC - 26 V DC (24 V DC Nominal)
Drop Out		6,9 V DC min.

Switching Time

Pull In		15 ms max.
Drop Out		10 ms max.
Life Expectancy		500.000 Operations min.

TOHTSU®

Right of techn. modifications is reserved


www.mecheltron.com

Technische Änderungen vorbehalten

Coaxial Relay TOHTSU



CX-140D-24V

Dimensions



Typical Operating Curves

Cable Mounting



Schematic

