

Coaxial Relay TOHTSU

CX-230-12V



Mechanical Characteristics

Contact Arrangement		SPDT
Operational Temperature		- 25 °C to + 50 °C
Max Temperature Rise		20 °C
Weight		Approx. 230 g
Mounting		Two screws
Cable Connections		3 BNC Type female connectors

Electrical Characteristics

Impedance		50 Ohms
Nominal Voltage		12 V DC
Voltage Range		10 V DC - 14 V DC
Current		160 mA @12 V DC 20 °C
Coil Resistance		75 ±10% Ohms @ 20 °C

RF-Properties

Frequency	VSWR	Isolation	Ins. Loss	RF Power input
MHz	max	-dB(min) ±3 dB	-dB(max)	W (PEP)
50	1.05	56	0.05	300
150	1.10	42	0.05	300
500	1.15	30	0.10	300
1000	1.30	24	0.20	200

Actuation Data

Pull In		10 V DC - 14 V DC (12 V DC Nominal)
Drop Out		3,0 V DC min.

Switching Time

Pull In		20 ms typ.
Drop Out		15 ms typ.
Life Expectancy		1.000.000 Operations min.

TOHTSU®

Right of techn. modifications is reserved


www.mecheltron.com

Technische Änderungen vorbehalten

Coaxial Relay TOHTSU





CX-230-12V

Dimensions



Typical Operating Curves

Schematic



TOHTSU®

Right of techn. modifications is reserved

www.mecheltron.com

Technische Änderungen vorbehalten