


Coaxial Relay TOHTSU

CX-570D-12V



Mechanical Characteristics

Contact Arrangement		SPDT
Operational Temperature		- 25 °C to + 50 °C
Max Temperature Rise		20 °C
Weight		Approx. 230 g
Mounting		Four screws
Cable Connections		3 TNC type female connectors

Electrical Characteristics

Impedance		50 Ω
Nominal Voltage		12 V DC
Voltage Range		10 V DC - 14 V DC
Current		160 mA @12 V DC 20 °C
Coil Resistance		75 $\Omega \pm 10\%$ @ 20 °C

RF-Properties

Frequency	VSWR	Isolation	Ins. Loss	RF Power input
MHz	max	-dB(min) ± 3 dB	-dB(max)	W (PEP)
50	1.005	65	0.010	350
150	1.010	60	0.015	300
500	1.030	53	0.018	300
1000	1.050	46	0.050	250
1500	1.170	42	0.050	200
2000	1.200	39	0.100	100

Actuation Data

Pull In		10 V DC - 14 V DC (12 V DC Nominal)
Drop Out		3.0 V DC min.

Switching Time

Pull In		20 ms max.
Drop Out		15 ms max.
Life Expectancy		1.000.000 Operations min.

TOHTSU®

Right of techn. modifications is reserved


www.mecheltron.com

Technische Änderungen vorbehalten


Coaxial Relay TOHTSU

CX-570D-12V


Dimensions




Typical Operating Curves



Cable Mounting



Schematic



TOHTSU

Right of techn. modifications is reserved

www.mecheltron.com

Technische Änderungen vorbehalten