


Coaxial Relay TOHTSU

CX-600N-24V



Mechanical Characteristics

Contact Arrangement		SPDT
Operational Temperature		- 25 °C to + 50 °C
Max Temperature Rise		20 °C
Weight		Approx. 230 g
Mounting		Four screws
Cable Connections		3 N type female connectors

Electrical Characteristics

Impedance		50 Ω
Nominal Voltage		24 V DC
Voltage Range		20 V DC - 26 V DC
Current		91 mA @24 V DC 20 °C
Coil Resistance		262 Ω ± 10% @ 20 °C

RF-Properties

Frequency	VSWR	Isolation	Ins. Loss	RF Power input
MHz	max	-dB(min) ±3 dB	-dB(max)	W (PEP)
50	1.03	60	0.07	1000
150	1.10	48	0.10	1000
500	1.15	37	0.15	800
1000	1.20	28	0.20	500
1500	1.25	26	0.20	350
2000	1.30	23	0.23	100

Actuation Data

Pull In		20 V DC - 26 V DC (12 V DC Nominal)
Drop Out		6.5 V DC min.

Switching Time

Pull In		20 ms max.
Drop Out		15 ms max.
Life Expectancy		500.000 Operations min.

TOHTSU®

Right of techn. modifications is reserved



www.mecheltron.com

Technische Änderungen vorbehalten

Coaxial Relay TOHTSU





CX-600N-24V

Dimensions



Typical Operating Curves

Schematic



TOHTSU®

www.mecheltron.com

Right of techn. modifications is reserved

Technische Änderungen vorbehalten